



True™ Series Displacement Chemicals Used to Effectively Clean Wellbore During OHGP Completion

True Series displacement chemicals offer effective mud removal while water-wetting tubulars in horizontal open-hole gravel pack completion.

CHALLENGE	SOLUTION	RESULT
<ul style="list-style-type: none"> • Perform direct displacement of SBM • Perform direct displacement of CleanDrill™ • Minimize post-displacement fluid system clean-up 	<ul style="list-style-type: none"> • Engineered True™ Series displacement chemical spacer train • ClearDepth™ displacement hydraulic modeling & WBCU tools • Systematic WBCU filtration process 	<ul style="list-style-type: none"> • Effectively & safely displaced wellbore multiple times • Water-wet tubulars • Achieved or exceeded fluid cleanliness performance specifications

OVERVIEW

In the Gulf of Mexico deepwater market, operators with horizontal open-hole gravel pack completions routinely use multiple types of fluids systems throughout the drilling and completion phases. These systems require seamless displacement or transition from one to the other through specifically designed procedures.

Extreme water depths require large marine risers making it problematic when cleaning up the wellbore and riser sections in a timely manner. A direct displacement is favored in order to accomplish the objectives of minimizing the volume and number of spacers pumped, maintaining hydrostatic control, and reducing rig circulating time. The selected rig for the operation was an ultra-deepwater, dual-activity drillship.

CHALLENGE

A major operator in the Gulf of Mexico required a solution to drill surface hole with spud mud, drill the intermediate hole sections with SBM, drill the reservoir section with a formation-friendly water-based RDF, and complete the well with reservoir compatible completion brine.

The proposed sequence of operations involved a direct displacement of 9.1 lb/gal Kronos™ low-ECD SBM to a 9.1 lb/gal CleanDrill™ water-based RDF and later to a 9.2 lb/gal KCl completion brine. This was a horizontal open-hole, gravel-pack completion with production casing to greater than 11,000' (3,353 meters) and open-hole to greater than 13,000' (3,962 meters). The operator set completion fluid cleanliness specifications for the displacement to completion brine at <30 NTUs out of the well and solids content at <0.05%.

Newpark used lab-tested chemistry and formulated the specific displacement chemical spacer train that separated the SBM drilling fluid from the water-based RDF, provided water-wetting to the tubulars, and then from the RDF to the completion fluid. The displacement hydraulics were modeled with ClearDepth™, which optimized the pump rates, annular velocities, and spacer contact times for each displacement sequence.

Archer wellbore cleanup (WBCU) tools were staged and placed for physical cleaning of the wellbore and Pro-T filtration equipment was incorporated, which allowed for the completion brine pump rates to be maintained for fluid cleanliness specifications.



SOLUTION

The rig surface fluid handling system was thoroughly cleaned of residual SBM in preparation to receive water-based RDF, while the drilling mud was circulated and conditioned to specifications prior to displacement. A True Series spacer train was formulated with TrueClean™ blended solvent/surfactant utilized in both the weighted transition and cleaning spacers. These concentrations were customized to the specific drilling mud being displaced.

Spacer	Type	Description	True Series Products	Density	Volume
1	Thinning	Base oil		6.8 lb/gal	150 bbls
2	Transition	Weighted push	TrueClean [solvent/surfactant]	10.2 lb/gal	359 bbls
3	Cleaning	Weighted cleaning	TrueClean [solvent/surfactant]	9.2 lb/gal	238 bbls
4	Viscous	Weighted viscosified	Cleanvis™ [Viscosifier]	9.2 lb/gal	159 bbls

The spacers were pumped down the workstring at a target rate of 9-10 bpm. The displacement spacer train was followed by CleanDrill RDF and continued until the water-based RDF was observed at the surface without issue. The open-hole section was then drilled to TD.

The displacement from CleanDrill to completion brine followed a similar procedure. The rig surface fluid handling system was thoroughly cleaned of residual water-based RDF in preparation to receive completion brine. A True Series spacer train was formulated with TrueSurf™ surfactant utilized in both of the cleaning spacers. These concentrations were customized to the specific water-based RDF being displaced.

Spacer	Type	Description	True™ Series Products	Density	Volume
1	Transition	Weighted push	TrueClean [solvent/surfactant]	9.2 lb/gal	359 bbls
2	Cleaning	Weighted cleaning	TrueClean [solvent/surfactant]	9.2 lb/gal	238 bbls
3	Viscous	Weighted viscosified	TrueCell™ [liquid HEC] TrueZan L [liquid Xanthan]	9.2 lb/gal	159 bbls
4	Flocculant	Weighted	TrueFloc™	9.2 lb/gal	150 bbls

The spacers were pumped down the kill line at a target rate of 10 bpm followed by the 9.2 ppg KCl completion brine. The boost line was engaged once the tail end of the displacement spacer train was greater than 100' above the boost line.

It was at this point that a target rate of 15 bpm down the boost line while circulating KCl completion brine was achieved. The pumping of 9.2 lb/gal KCl completion brine continued past the point it was observed at surface until it reached cleanliness specifications, which was an additional 90 minutes.

The workstring and riser WBCU tool assemblies were pulled out of the hole prior to the displacement; however, the riser had been sufficiently scraped and brushed. The well filter tools captured associated debris for removal. With the available pit space, all required completion fluid was on surface and within fluid cleanliness specifications prior to the displacement to avoid the need to filter while displacing.

RESULTS

All spacers returned to the surface when expected. The total displacement time was 7.25 hours. There was just a little over 1.5x well volumes circulated. The final fluid clarity endpoint result was 16 NTUs and <0.05% solids out of the well, which satisfied the specified target established by the operator. The use of specific chemistries coupled with reliable hydraulics modeling, robust WBCU tool and proper filtration resulted in multiple successful displacements.