PRODUCT BULLETIN





PRODUCT DESCRIPTION

EvoCon® fluid conditioner is a water-based fluid stabilizer used as a primary component of the Evolution® fluid system, Newpark's proprietary high-performance water-based drilling fluid technology. The polymer-based, clay-free Evolution fluid system is designed specifically for drilling unconventional horizontal wells.

BENEFITS

In the Evolution system, EvoCon fluid conditioner optimizes the performance of both EvoVis® viscosifier and EvoLube® DPE performance enhancer.

APPLICATION

The product should be used in the system's initial formulation, with the concentrations maintained consistently in the system.

TREATMENT RECOMMENDATION

EvoCon fluid conditioner is used in concentrations ranging from 0.25-3.0 lb/bbl.

TYPICAL PHYSICAL PROPERTIES

Appearance	Light amber liquid
Flash Point	545°F (285°C)
Specific Gravity	1.0-1.1

HANDLING AND STORAGE

EvoCon conditioner is slippery. Use caution around spills. Avoid inhalation of fumes. Avoid contact with skin and eyes. Keep containers tightly closed in a dry, cool, and well-ventilated area. Use appropriate hygiene, clothing and personal protective equipment suitable for work being done. Review the SDS thoroughly before using this product.

PACKAGING

EvoCon fluid conditioner is available in 5-gallon (19-liter) pails, 55-gallon (208) drums and 275 gallon (1,041 liter) totes.

Evolution is a registered trademarks of Newpark Drilling Fluids LLC in the United States. These trademarks may also be registered in other countries.

This document is supplied solely for informational purposes and Newpark Drilling Fluids makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data.

All product warranties and guarantees shall be governed by the General Terms and Conditions.