

NoFoam™ X

DEFOAMER



NEWPARK
DRILLING FLUIDS

www.newparkdf.com

PRODUCT DESCRIPTION

NoFoam™ X defoamer is a blend of defoaming agents.

BENEFITS

In addition to controlling surface foaming, NoFoam X additive also acts to prevent foam from developing and allow entrapped air to break out of the drilling fluid.

APPLICATION

NoFoam X defoamer is effective in all types of water-based drilling fluids to control both surface foaming and entrapped air.

TREATMENT RECOMMENDATION

To control surface foam, the product should be splashed on the surface of the fluid system. Alternatively, the product can be slowly trickled above the mud trough through a small hole in the bottom of the pail.

TYPICAL PHYSICAL PROPERTIES

Appearance..... Milky, viscous liquid

Flash Point.....400°F (204°C)

Specific Gravity.....0.9–1.0

HANDLING AND STORAGE

NoFoam X is very slippery. Use caution around spills. Store away strong oxidizing agents and strong acids. Keep container tightly closed to protect from atmospheric moisture. Use appropriate hygiene, clothing and personal protective equipment suitable for work being done. Review the SDS thoroughly before using this product.

PACKAGING

NoFoam X defoamer is available in 5-gallon (19-liter) pails.

This document is supplied solely for informational purposes and Newpark Drilling Fluids makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data.

All product warranties and guarantees shall be governed by the General Terms and Conditions.